


APPROXIMATE WEIGHTS:
TOP - 27,000 LBS.
BASE - 29,000 LBS.

OVERALL DIMENSIONS:
INSIDE LENGTH - 14'
INSIDE WIDTH - 8'-0"
INSIDE HEIGHT - 9'-6"
OUTSIDE LENGTH - 15'
OUTSIDE WIDTH - 9'
OUTSIDE HEIGHT - 10'-8"

NOTES:

1. LOCATE VAULT AS DIRECTED BY C.O.B. ELECTRIC UTILITY.
2. INSTALL GROUNDING SYSTEM PER C.O.B. STANDARD DRAWING #600-21.
3. INSTALL A MINIMUM 8" OF 3/4" CRUSHED ROCK UNDER VAULT.
4. ALLOW UP TO 3" OF EXTRA EXCAVATION DEPTH FOR ADJUSTING LID UP TO FINAL GRADE.
5. BACKFILL AROUND STRUCTURE WITH ONE-SACK CEMENT SLURRY TO WITHIN ONE FOOT OF FINAL GRADE.
6. INSTALL LADDER INSIDE VAULT, DIRECTLY UNDER MANHOLE OPENING.
7. PROVIDE UNOBSTRUCTED SPACE CLEARANCES AROUND VAULT PER SD #600-72.

REF: 3325.1



REVISED: 08/13/2019

APPROVED: *[Signature]*

STANDARD DRAWINGS

PRECAST CONCRETE MANHOLE
BODY, 8' x 14' x 9'-6"

SD

600-57